

**FLAMMABLE LIQUID STORAGE CABINET - 350LTR, 2 DOORS, 3 SHELVES**

**PRODUCT CODE: 5560AS**

Pratt Indoor Flammable Liquid Storage Cabinets comply with the Australian Standard AS 1940-2017 “The Storage and Handling of Flammable and Combustible Liquids” in accordance with the cabinet specifications detailed in Clause 4.9.

This range of cabinets provide a fire resistant enclosure and help with good house-keeping practices. They are suitable for indoor storage of all flammable and combustible liquids as defined by the United Nations criteria and the Australian ADG Code for Dangerous Goods. For example: Petrol, Diesel, Paints, Solvents, Thinners, Kerosene, Turpentine, White Spirits, Alcohol and Ethanol etc. They are also suitable for the storage of Aerosols where additional fire protection is required.

**FEATURES AND BENEFITS:**

- Constructed of double walled 1.2mm thick galvanised steel.
- 2 x Sequential self closing doors fitted with speed adjustable hydraulic closures.
- 3 x 1.6mm thick, perforated, galvanised steel shelves.
- Continual stainless steel piano type door hinges.
- Overlapping door edging to prevent ingress of heat.
- Adjustable shelf heights at 90mm increments.
- 2 x 50mm vent bungs with steel caps.
- Each vent incorporates steel flash arrester.
- 3 point self latching door mechanism.
- Recessed handle with keyed alike lock with 2 keys.
- External static earth connection and 1 x earthing wire.
- Solvent resistant yellow baked powder coated finish.
- 150mm deep liquid tight sump.
- Palletized and packaged with strong cardboard for protection during transportation and storage.
- Flammable Liquid diamond and other decals applied.
- Optional additional shelves available.

**Weight:** 230kg

**Capacity:** 350L

**Doors:** 2

**Shelves:** 3 (Inc. Base Level)

**Extra Shelf:** 5560-29S



EXTERNAL (mm)			INTERNAL (mm)		
HEIGHT	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH
1825	1440	585	1545	1350	495

**Note:** 1. For all two door cabinets, the internal height is taken from the top of sump sill/bottom shelf to the sequential chassis assembly.  
2. For total external width measurement, add 6mm per vent bung for tight clearance locations.

VOLUME CAPACITY	PER SHELF	TOTAL
2L Winchester	30	90
4L Winchester	16	48
4L Paint Can	14	42
20L Round Can	4	12
Aerosol Can	140	420